# Dynamic Proxies

David Rabinowitz

## Dynamic Proxies

- Support for creating classes at runtime
  - Each such class implements interface(s)
  - Every method call to the class will be delegated to a handler, using reflection
  - The created class is a proxy for its handler
- Applications
  - Aspect-Oriented Programming: standard error handling, log & debug for all objects
  - Creating dynamic event handlers



## Invocation Handlers

- Start by defining the handler:
  - `interface java.lang.reflect.InvocationHandler`
  - With a single method:

```
Object invoke(      // return value of call
  Object proxy,     // call's target
  Method method,    // the method called
  Object[] args)    // method's arguments
```

- The "real" call made: `proxy.method(args)`
  - Simplest invoke(): `method.invoke(proxy,args)`



## Creating a Proxy Class

- Define the proxy interface:

```
interface Foo { Object bar(Object obj); }
```

- Use `java.lang.reflect.Proxy` static methods to create the proxy class:

```
Class proxyClass = Proxy.getProxyClass(
    Foo.class.getClassLoader(), new
  Class[] { Foo.class });
```

- First argument - the new class's class loader
- 2nd argument - list of implemented interfaces
- The expression *C.class* for a class C is the static version of *C_obj.getClass()*

## Creating a Proxy Instance

- A proxy class has one constructor which takes one argument - the invocation handler
- Given a proxy class, find and invoke this constructor:

```
Foo foo = (Foo)proxyClass.
   getConstructor(new Class[] { InvocationHandler.class }).
   newInstance(new Object[] { new MyInvocationHandler() });
```

- Class Proxy provides a shortcut:

```
Foo f = (Foo) Proxy.newProxyInstance(
                              Foo.class.getClassLoader(),
                              new Class[] { Foo.class },
                              new MyInvocationHandler());
```



## A Few More Details

- We ignored a bunch of exceptions
  - *IllegalArgumentException* if proxy class can't exist
  - *UndeclaredThrowableException* if the handler throws an exception the interface didn't declare
  - *ClassCastException* if return value type is wrong
  - *InvocationTargetException* wraps checked exceptions
- A proxy class's name is undefined
  - But begins with Proxy$
- Primitive types are wrapped by *Integer*, *Boolean*, and so on for argument and return values
- The syntax is very unreadable!
  - Right, but it can be encapsulated inside the handler



## A Debugging Example

- We'll write an extremely generic class, that can wrap any object and print a debug message before and after every method call to it
- Instead of a public constructor, it will have a static factory method to encapsulate the proxy instance creation
- It will use **`InvocationTargetException`** to be exception-neutral to the debugged object



## A Debugging Example II

- The class's definition and construction:

```
public class DebugProxy
implements java.lang.reflect.InvocationHandler {
     private Object obj;
     public static Object newInstance(Object obj) {
        return
java.lang.reflect.Proxy.newProxyInstance(
                  obj.getClass().getClassLoader(),
                  obj.getClass().getInterfaces(),
                  new DebugProxy(obj)); }
   private DebugProxy(Object obj) { this.obj = obj;
}
```

## A Debugging Example III

- The invoke() method:

```
public Object invoke(Object proxy, Method m,
                                   Object[] args) throws
Throwable {
  Object result;
  try {
    System.out.println("before method " + m.getName());
    result = m.invoke(obj, args);
  } catch (InvocationTargetException e) {
    throw e.getTargetException();
  } catch (Exception e) {
    throw new RuntimeException("unexpected:" +
      e.getMessage());
  } finally {
        System.out.println("after method " + m.getName());
  }
   return result; }
```



## A Debugging Example IV

- Now that the handler is written, it's very simple to use. Just define an interface:

```
interface Foo { Object bar(Object o); }
class FooImpl implements Foo { … }
```

- And wrap it with a DebugProxy:

```
Foo foo = (Foo)DebugProxy.newInstance(new
FooImpl());
```

- This is not much different than using any proxy or decorator
- Just much, much slower



## Dynamic Proxies: Summary

- Applications similar to above example:
  - Log every exception to a file and rethrow it
  - Apply an additional security policy
- Other kinds of applications exist as well
  - Dynamic event listeners in Swing
  - In general, being an observer to many different objects or interfaces at once
- It's a relatively new feature – from JDK 1.3
  - There may be other future applications



## More Information

- http://java.sun.com/j2se/1.4.2/docs/guide/reflection/proxy.html
- http://java.sun.com/j2se/1.4.2/docs/api/java/lang/reflect/Proxy.html